

# Linodur

## operation area

|                   |   |
|-------------------|---|
| <b>Procedure:</b> | Coating / care  |
| <b>Surfaces:</b>  | all water-resistant coverings such as e.g. B. PVC, linoleum, rubber and other plastic floors and natural stone (e.g. marble) and Artificial stone floors (e.g.: terrazzo), (acrylic lacquer) sealed parquet floors, Screed floors (after priming with pore filler) etc. |
| <b>A notice:</b>  | Not suitable for unsealed wood and cork surfaces as well factory-made PUR-coated coverings.   |



Item No. g0650

canister

10 L

## load level



**pH=8**

in the concentrate

### Characteristics

- § High filling power with open-pore coverings
- § Satin finish
- § Anti-slip and suitable for high speeds
- § Low-foaming - to avoid disturbances during counteract film formation

### advantages

- § Soft coating, therefore very good properties
- § Scratches e.g. from chairs, tables etc.
- § Sure-footed
- § Easily removable
- § Especially for linoleum and rubber flooring
- § Very polishable due to the high wax content

## sustainability and ecology

Sustainability and careful use of the environment and resources have always been the focus at hollu. As a specialist in We ensure that cleaning products and solutions for commercial users are ecologically compatible – from the Raw material selection and production to delivery. At the same time, we support our customers with training courses, detailed Cleaning plans and the latest dosing technologies in daily product use - for the benefit of economy and ecology. This We prove this through certification according to ISO 14001 (environmental management system) and EMAS certification. We also take into account the careful use of energy and water and the recyclability of our packaging materials. The bundles exist made of PE and recyclable cardboard and can be disposed of at the appropriate waste collection points. canisters can be returned empty.

## application



Prerequisite: Thoroughly cleaned, neutralized and dry floor covering (free of surfactants). Allow underfloor heating to cool down in good time / close windows.

Perform coating: Apply thinly and evenly, preferably with hollu Met-Wiesel. Further applications are only possible after complete drying (approx. 20 - 30 minutes). For new coatings apply 1-2 times. The protective film can be fully loaded after 1-2 days. Wipe new coatings with a damp cloth for approx. 1 week using only clear water.



## dosage

undiluted

## Range

Approx. 20-35 m<sup>2</sup> can be coated with 1 L of coating.  
Depending on the absorbency of the covering.

## Compatible system products



55821 - Mead weasel, without stem; 55822 - Met Strip, cover; (suitable handles: item no. 56966, 56967, 56968 or 56969)

## storage notice

The product can be stored in the temperature range from 4 °C to +40 °C. Shelf life: 2 years. Opened containers: For the storage of product residues, it is advisable to fill them into smaller containers so that as little air as possible is trapped in the container.

The text of this product information corresponds to the current status of our technical knowledge and experience and is intended to advise you to the best of our knowledge and belief. However, due to the variety of working methods, material properties and application, it is not a legally binding guarantee of specific properties!

[www.hollu.com](http://www.hollu.com)

**hollu Systemhygiene GmbH** A-6170

Zirl | Salzstrasse 6 | Phone +43 5238 52800 | Fax -990 | Email: [info@hollu.com](mailto:info@hollu.com) ©

hollu Systemhygiene GmbH | Product sheet | 04/2019 Errors, typographical and printing errors, as well as changes reserved.

so geht sauber. **hollu**