

Met Hospital


operation area

- Procedure:** Coating / care
- Surfaces:** all water-resistant coverings such as e.g. B. PVC, linoleum, rubber and other plastic floors and natural stone (e.g. marble) and Artificial stone floors (e.g.: terrazzo), (acrylic lacquer) sealed parquet floors, Screed floors (after priming with pore filler) etc.
- A notice:** Not suitable for unsealed wood and cork surfaces as well factory-made PUR-coated coverings.



Item No. g0660 canister 10 L

load level



pH = 9

in the concentrate

Characteristics

- § Alcohol resistant
- § High-gloss finish
- § Makes the surface hydrophobic
- § Suitable for high speed
- § Low-foaming - to avoid disturbances during counteract film formation.

advantages

- § Ideal for areas facing high resistance request disinfectants
- § Hard and wear-resistant coating
- § Excellent course

sustainability and ecology

Sustainability characterizes everything we think and do, as evidenced by the ISO 14001 and EMAS certifications, among other things. Also in Throughout the product life cycle, we pay attention to the careful use of the environment and resources: from the selection of raw materials to the Production and delivery up to the automatic removal of the hollu empty containers and recycling. The hollu bundles consisting made of PE and cardboard, can also be disposed of completely empty at the appropriate waste collection points.

application



Prerequisite: Thoroughly cleaned, neutralized and dry floor covering (free of surfactants). Allow underfloor heating to cool down in good time / close windows.

Perform coating: Apply thinly and evenly, preferably with hollu Met-Wiesel. Further applications are only possible after complete drying (approx. 20 - 30 minutes). For new coatings apply 1-2 times. The protective film can be fully loaded after 1-2 days. Wipe new coatings with a damp cloth for approx. 1 week using only clear water.



Instructions for **use:** Any

further treatment (e.g. polishing) can affect the properties.

dosage

undiluted

Range

Approx. 20-35 m² can be coated with 1 L of coating.
Depending on the absorbency of the covering.

Compatible system products



55821 - Mead weasel, without stem; 55822 - Met Strip, cover; (suitable handles: item no. 56966, 56967, 56968 or 56969)

storage notice

The product can be stored in the temperature range from 4 °C to +40 °C. Shelf life: 2 years. Opened containers: For the storage of product residues, it is advisable to fill them into smaller containers so that as little air as possible is trapped in the container.

The text of this product information corresponds to the current status of our technical knowledge and experience and is intended to advise you to the best of our knowledge and belief. However, due to the variety of working methods, material properties and application, it is not a legally binding guarantee of specific properties!

www.hollu.com

hollu Systemhygiene GmbH A-6170

Zirl | Salzstrasse 6 | Phone +43 5238 52800 | Fax -990 | Email: info@hollu.com ©

hollu Systemhygiene GmbH | Product sheet | 04/2019 Errors, typographical and printing errors, as well as changes reserved.

so geht sauber. **hollu**